

Fluke Networks Manufacturing  
Everett, Washington, USA

## Certificate of Calibration

Model  
**DTX-1800**

S/N  
**1581061**

Date of Calibration  
**02-02-2011**

**Fluke Networks**  
PO Box 777  
Everett, WA  
98206-0777

**phone**  
425.347.6100

**fax**  
425.446.5043

Fluke Networks, a division of Fluke Corporation, NQA ISO 9001:2000 ISO Certificate No. 10100, hereby certifies that the products identified above have been tested and calibrated during the manufacturing process using standard Fluke Networks procedures, measurement standards and test equipment. Its calibration processes are ISO-9001 controlled and are designed to certify that the instrument listed above meets the published specifications.


Fluke Networks further certifies that the measurement standards and instruments used during the calibration of this product are traceable to the United States National Institute of Standards and Technology (NIST).

This certificate applies only to the items identified and shall not be reproduced other than in full, without the specific written approval by Fluke Networks.

The calibration cycle of the DTX Series CableAnalyzers™ and the Fiber Optic Loss Test modules is one year. These products are sold through distribution channels and Fluke Networks does not and cannot control the flow of the product through these channels. The start of the calibration cycle can be counted on the day the products are placed into service as long as they have been stored for six months or less under environmental conditions specified by Fluke Networks in the Technical Reference Handbook, Chapter 9 Maintenance and Specifications, Storage temperature range -20°C to +60°C (-4°F to +140°F).

- If the products identified above have been stored for six months or less under the specified environmental conditions, the date of the purchase invoice of the DTX units by the end user will be counted as the date the product has been put into service and as the start date for the calibration cycle. The product is due for calibration on or before the anniversary of that date.
- If the products have been stored under the specified environmental conditions for a period over six months, the calibration cycle is started six months after the date of calibration printed above and the product is due for calibration on or before the anniversary of that date.

Authorized Signature:



Donovan Pfeifer Quality Manager, Certification Products

02-04-2011 07:46:25

Date

### Standards Used

Artifact Set: RemoteNEXT=1413118, FEXT=1413144, RemoteRL=1413138, Cable=1413153 Set calibrated on 10/10/2010. Due for calibration on 10/10/2011  
Test Partner: DTX-1800R S/N 1581062

### Test Procedure

Procedure: DTX Automated Final Test Version: 15-Jun-2005 Program: UluTest v1.2.022 Aug 22, 2007

Page 1 of 1